



The Choice of Professionals

King Bros. Industries

29101 The Old Road, Valencia, CA 91355
Toll Free: (800) 325-9468 Fax: (661) 257-4320
E-mail: valves@kbico.com Web: www.kbico.com

CPVC Water Hammer Arrestor

Features:

- KBI type "AA" water hammer arrestor valves are molded in the USA for use in hot and cold water distribution systems.
- Designed to limit pressure shock developed by quick acting valves.
- Pressure rated to 400 psi @ 73°F and 180 psi @ 180°F.
- Approved for use with **PlatinumXCELL**® and all other CPVC CTS plumbing systems.
- All plastic corrosion resistant design.
- Spigot end meets ASTM D2846 specifications.
- NSF-61 listed as safe for potable water systems.
- ASSE 1010 listed.
- UPC listed.
- Lead Free.



Model	Size	Description	Case	Weight
CHA-0500	1/2"	CTS Spigot inlet	100	Call

FEATURES COMMON TO KBI CPVC PLUMBING PRODUCTS

- NSF listed *
- IAPMO (UPC) listed *
- Molded in the USA by KBI
- Pressure rated to 100 psi @ 180°F
- Meets/Exceeds all ASTM Standards
- Made with PlatinumXCELL® CPVC
- Limited LIFETIME Warranty

